

PRODUCT INFORMATION (*)	
-------------------------	--

ROOM AIR CONDITIONER	INDOOR MODEL	MSZ-EF50VGW / MSZ-EF50VGS / MSZ-EF50VGB
	OUTDOOR MODEL	MUZ-EF50VG

Function (indicate if present)		If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.
cooling	Y	
heating	Y	

Item	symbol	value	unit	Item	symbol	value	unit
Design load				Seasonal efficiency			
cooling	Pdesignnc	5.0	kW	cooling	SEER	7.5	-
heating/Average	Pdesignnh	4.2	kW	heating/Average	SCOP/A	4.5	-
heating/Warmer	Pdesignnh	2.3	kW	heating/Warmer	SCOP/W	5.4	-
heating/Colder	Pdesignnh	x	kW	heating/Colder	SCOP/C	x	-

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	5.0	kW
Tj=30°C	Pdc	3.7	kW
Tj=25°C	Pdc	2.4	kW
Tj=20°C	Pdc	1.6	kW

Declared energy efficiency ratio, at indoor temperature 27(19) °C and outdoor temperature Tj			
Tj=35°C	EERd	3.3	-
Tj=30°C	EERd	5.3	-
Tj=25°C	EERd	8.5	-
Tj=20°C	EERd	16.5	-

Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	3.8	kW	Tj=-7°C	COPd	2.8	-
Tj=2°C	Pdh	2.3	kW	Tj=2°C	COPd	4.6	-
Tj=7°C	Pdh	1.4	kW	Tj=7°C	COPd	5.8	-
Tj=12°C	Pdh	0.7	kW	Tj=12°C	COPd	5.4	-
Tj=bivalent temperature	Pdh	4.2	kW	Tj=bivalent temperature	COPd	2.5	-
Tj=operating limit	Pdh	3.5	kW	Tj=operating limit	COPd	1.9	-

Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	2.3	kW	Tj=2°C	COPd	4.6	-
Tj=7°C	Pdh	1.4	kW	Tj=7°C	COPd	5.8	-
Tj=12°C	Pdh	0.7	kW	Tj=12°C	COPd	5.4	-
Tj=bivalent temperature	Pdh	2.3	kW	Tj=bivalent temperature	COPd	4.6	-
Tj=operating limit	Pdh	3.5	kW	Tj=operating limit	COPd	1.9	-

Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	x	kW
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW
Tj=-15°C	Pdh	x	kW

Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	x	-
Tj=2°C	COPd	x	-
Tj=7°C	COPd	x	-
Tj=12°C	COPd	x	-
Tj=bivalent temperature	COPd	x	-
Tj=operating limit	COPd	x	-
Tj=-15°C	COPd	x	-

Bivalent temperature			
heating/Average	Tbiv	-10	°C
heating/Warmer	Tbiv	2	°C
heating/Colder	Tbiv	x	°C

Operating limit temperature			
heating/Average	Tol	-15	°C
heating/Warmer	Tol	-15	°C
heating/Colder	Tol	x	°C

Cycling interval capacity			
for cooling	P _{cycc}	x	kW
for heating	P _{psych}	x	kW
Degradation co-efficient cooling	C _{dc}	0.25	-

Cycling interval efficiency			
for cooling	EER _{cycc}	x	-
for heating	COP _{cycc}	x	-
Degradation co-efficient heating	C _{dh}	0.25	-

Electric power input in power modes other than 'active mode'			
off mode	P _{OFF}	1	W
standby mode	P _{SB}	1	W
thermostat - off mode	P _{TO}	8	W
crankcase heater mode	P _{CK}	0	W

Annual electricity consumption			
cooling	Q _{CE}	233	kWh/a
heating/Average	Q _{HE}	1304	kWh/a
heating/Warmer	Q _{HE}	595	kWh/a
heating/Colder	Q _{HE}	x	kWh/a

Capacity control (indicate one of three options)	
fixed	N
staged	N
variable	Y

Other items			
Sound power level (indoor/outdoor)	L _{WA}	60/65	dB(A)
Global warming potential	GWP	550	kgCO ₂ eq.
Rated air flow (indoor/outdoor)	-	678/2412	m ³ /h

Contact details for obtaining more information	Name and address of the manufacturer or of its authorized representative.
--	---

(*) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.